



Revision Number: 001.1

Issue date: 11/04/2010

**1. PRODUCT AND COMPANY IDENTIFICATION**

|                               |  |                     |               |
|-------------------------------|--|---------------------|---------------|
| <b>Product name:</b>          | <b>FREKOTE B-15 SEALER 5 GA PA</b>             | <b>IDH number:</b>  | 420431        |
| <b>Product type:</b>          | Mold Release                                   | <b>Item number:</b> | 83494         |
|                               |  | <b>Region:</b>      | United States |
| <b>Company address:</b>       | <b>Contact information:</b>                    |                     |               |
| Henkel Corporation            | Telephone: 860.571.5100                        |                     |               |
| One Henkel Way                | MEDICAL EMERGENCY Phone: Poison Control Center |                     |               |
| Rocky Hill, Connecticut 06067 | 1-877-671-4608 (toll free) or 1-303-592-1711   |                     |               |
|                               | TRANSPORT EMERGENCY Phone: CHEMTREC            |                     |               |
|                               | 1-800-424-9300 (toll free) or 1-703-527-3887   |                     |               |
|                               | Internet: www.henkelna.com                     |                     |               |

Contains one or more components for which a Toxic Substances Control Act (TSCA) Low Volume Exemption (LVE) applies. See Section 15.

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

|                        |                           |                             |                    |
|------------------------|---------------------------|-----------------------------|--------------------|
| <b>Physical state:</b> | Liquid                    | <b>HMIS:</b>                |                    |
| <b>Color:</b>          | Colorless                 | <b>HEALTH:</b>              | *2                 |
| <b>Odor:</b>           | Mild, Solvent, Ether-like | <b>FLAMMABILITY:</b>        | 3                  |
|                        |                           | <b>PHYSICAL HAZARD:</b>     | 0                  |
|                        |                           | <b>Personal Protection:</b> | See MSDS Section 8 |

**WARNING:** FLAMMABLE LIQUID AND VAPOR.  
MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS.  
MAY BE HARMFUL IF SWALLOWED, ABSORBED THROUGH SKIN OR INHALED.  
CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.  
ASPIRATION HAZARD IF SWALLOWED.  
CAN ENTER LUNGS AND CAUSE DAMAGE.

**Relevant routes of exposure:** Skin, Inhalation, Eyes, Ingestion

**Potential Health Effects**

|                      |  |
|----------------------|--|
| <b>Inhalation:</b>   | Vapors and mists will irritate nose and throat and possibly eyes. Breathing small amounts during normal handling is not likely to cause harmful effects; breathing large amounts may be harmful. May cause central nervous system effects, such as headache, nausea, vomiting, abdominal pain, dizziness, confusion, and breathing difficulties. |
| <b>Skin contact:</b> | Solvent action can dry and defat the skin, causing the skin to crack, leading to dermatitis.   |
| <b>Eye contact:</b>  | Moderate eye irritation. Liquid or vapor can cause moderate to severe irritation.  |
| <b>Ingestion:</b>    | May be harmful if swallowed. Aspiration may occur during swallowing or vomiting, resulting in lung damage. Central nervous system depression, including dizziness, drowsiness, fatigue, nausea, headache, unconsciousness.   |

**Existing conditions aggravated by exposure:** Dermatitis. Eczema. Other pre-existing skin conditions. Asthma. Other respiratory disorders (bronchitis, emphysema, bronchial hyperreactivity).

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous components | CAS NUMBER  | %        |
|----------------------|-------------|----------|
| Dibutyl ether        | 142-96-1    | 60 - 100 |
| Proprietary Resin    | Proprietary | 1 - 5    |

### 4. FIRST AID MEASURES

|                      |  |
|----------------------|--|
| <b>Inhalation:</b>   | Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.   |
| <b>Skin contact:</b> | Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and footwear. Wash clothing before reuse. If skin irritation persists, call a physician.  |
| <b>Eye contact:</b>  | Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. Get immediate medical attention.   |
| <b>Ingestion:</b>    | Keep individual calm. Do not induce vomiting: contains petroleum distillates and/or aromatic solvents. If vomiting occurs, prevent aspiration by keeping the patient's head below the knees. Never give anything by mouth to an unconscious person. Get immediate medical attention. |

### 5. FIRE FIGHTING MEASURES

|  |   |
|--|---|
| <b>Flash point:</b>                        | 25 °C (77°F) Tagliabue closed cup   |
| <b>Autoignition temperature:</b>           | 194 °C (381.2 °F)   |
| <b>Flammable/Explosive limits - lower:</b> | 1.5 % (value for solvent)   |
| <b>Flammable/Explosive limits - upper:</b> | 7.6 % (value for solvent)   |
| <b>Extinguishing media:</b>                | Water spray (fog), foam, dry chemical or carbon dioxide. Do not use high volume water jet.  |
| <b>Special firefighting procedures:</b>    | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Water may be unsuitable as an extinguishing media, but may be helpful in keeping adjacent containers cool. Keep personnel upwind of fire.  |
| <b>Unusual fire or explosion hazards:</b>  | Vapors may form explosive mixtures with air. Do not handle or store near an open flame, heat or other sources of ignition. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a significantly high level, sparks can form that may ignite vapors of flammable liquids. This product may form explosive peroxides. |
| <b>Hazardous combustion products:</b>      | Oxides of carbon. Irritating organic vapours. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  |

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |  |
|-----------------------------------|--|
| <b>Environmental precautions:</b> | Do not allow product to enter sewer or waterways. Advise authorities if product has entered or may enter sewers, water sources or extensive land areas. Prevent further leakage or spillage. This product is insoluble in water and will float on surface. |
|-----------------------------------|--|

**Clean-up methods:**

Remove all sources of ignition. Ventilate area. Keep upwind of the spilled material and isolate exposure. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Store in a closed metal container until ready for disposal. Use non-sparking tools for clean-up. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

## 7. HANDLING AND STORAGE

**Handling:**

During use and until all vapors are gone: Keep area ventilated - do not smoke; extinguish all flames, pilot lights, and heaters; turn off stoves, electrical tools and appliances, and any other sources of ignition. Do not breathe gas/fumes/vapor/spray. Avoid contact with eyes, skin and clothing. For operations where eye or face contact could occur, provide safety shower and eyewash fountain. Wash thoroughly after handling. Make sure containers are properly grounded before use or transfer of material. Refer to Section 8.

**Storage:**

For safe storage, store at or below 48.8 °C (119.8 °F)  
Store away from heat, sparks, flames, or other sources of ignition. Keep container closed.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous components | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|----------------------|-----------|----------|-----------|-------|
| Dibutyl ether        | None      | None     | None      | None  |
| Proprietary Resin    | None      | None     | None      | None  |

**Engineering controls:**

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination.

**Respiratory protection:**

Use a NIOSH approved respirator if ventilation is inadequate.

**Eye/face protection:**

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:**

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|   |                                   |
|---|-----------------------------------|
| <b>Physical state:</b>                          | Liquid                            |
| <b>Color:</b>                                   | Colorless                         |
| <b>Odor:</b>                                    | Mild, Solvent, Ether-like         |
| <b>Odor threshold:</b>                          | Not available                     |
| <b>pH:</b>                                      | Not available                     |
| <b>Vapor pressure:</b>                          | 4.8 mm hg (20 °C (68°F))          |
| <b>Boiling point/range:</b>                     | > 141 °C (> 285.8 °F) (1,013 hPa) |
| <b>Melting point/ range:</b>                    | Not available                     |
| <b>Specific gravity:</b>                        | 0.769                             |
| <b>Vapor density:</b>                           | Heavier than air.                 |
| <b>Flash point:</b>                             | 25 °C (77°F) Tagliabue closed cup |
| <b>Flammable/Explosive limits - lower:</b>      | 1.5 % (value for solvent)         |
| <b>Flammable/Explosive limits - upper:</b>      | 7.6 % (value for solvent)         |
| <b>Autoignition temperature:</b>                | 194 °C (381.2 °F)                 |
| <b>Evaporation rate:</b>                        | Slower than ether.                |
| <b>Solubility in water:</b>                     | Not miscible or difficult to mix  |
| <b>Partition coefficient (n-octanol/water):</b> | Not available                     |
| <b>VOC content:</b>                             | 99.5 %; 746 g/l                   |

## 10. STABILITY AND REACTIVITY

|  |  |
|--|--|
| <b>Stability:</b>                        | May form explosive peroxides with prolonged exposure to air or oxygen, especially under anhydrous conditions. Risk of ignition. Stable under normal conditions of storage and use.   |
| <b>Hazardous reactions:</b>              | Will not occur.  |
| <b>Hazardous decomposition products:</b> | Peroxides. Hydrocarbons.   |
| <b>Incompatible materials:</b>           | Oxidizing agents may form explosive peroxides. Strong oxidizing agents. Strong acids and strong bases.   |
| <b>Conditions to avoid:</b>              | Keep away from open flames, hot surfaces and sources of ignition. Vapors may form explosive mixtures with air. Fire or intense heat may cause violent rupture of packages. Spray mist may be flammable at temperatures below the flash point. Will slowly degrade with exposure to oxygen (air). Avoid static discharge. |

## 11. TOXICOLOGICAL INFORMATION

| Hazardous components | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|----------------------|----------------|-----------------|--|
| Dibutyl ether        | No             | No              | No                                       |
| Proprietary Resin    | No             | No              | No                                       |

| Hazardous components | Health Effects/Target Organs   |
|----------------------|--|
| Dibutyl ether        | Irritant, Central nervous system, Cardiac, Kidney, Gastrointestinal, Mutagen |
| Proprietary Resin    | No Data  |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available

## 13. DISPOSAL CONSIDERATIONS

**Information provided is for unused product only.**

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** D001: Ignitable.

## 14. TRANSPORT INFORMATION

The shipping classification in this section are for bulk packaging only. Shipping classification may be different for non-bulk packaging as exceptions may apply. Refer to shipping documents for package specific transportation classification.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Resin solution  
**Hazard class or division:** 3  
**Identification number:** UN 1866  
**Packing group:** III

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Resin solution  
**Hazard class or division:** 3  
**Identification number:** UN 1866  
**Packing group:** III

**Water Transportation (IMO/IMDG)**

|                           |                |
|---------------------------|----------------|
| Proper shipping name:     | RESIN SOLUTION |
| Hazard class or division: | 3              |
| Identification number:    | UN 1866        |
| Packing group:            | III            |

**15. REGULATORY INFORMATION**

**United States Regulatory Information**

|  |  |
|--|--|
| <b>TSCA 8 (b) Inventory Status:</b>    | All components of this product are listed on the U.S. Toxic Substances Control Act (TSCA) inventory or are exempt from listing because a Low Volume Exemption (LVE) has been granted in accordance with 40 CFR 723.50. |
| <b>TSCA 12(b) Export Notification:</b> | None above reporting de minimus  |
| <b>CERCLA/SARA Section 302 EHS:</b>    | None above reporting de minimus  |
| <b>CERCLA/SARA Section 311/312:</b>    | Immediate Health, Fire   |
| <b>CERCLA/SARA 313:</b>                | None above reporting de minimus  |
| <b>California Proposition 65:</b>      | No California Proposition 65 listed chemicals are known to be present.   |

**Canada Regulatory Information**

|                              |   |
|------------------------------|---|
| <b>CEPA DSL/NDSL Status:</b> | One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List. |
| <b>WHMIS hazard class:</b>   | B.2, D.2.B  |

**16. OTHER INFORMATION**

This material safety data sheet contains changes from the previous version in sections: 1, 3, 10, 11

Prepared by: Katherine Caddy, Regulatory Affairs Specialist

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.